Pellet Inserts



BY FORGE & FLAME

Harman Pellet Inserts

Packed with exclusive technologies, Harman pellet inserts give you the most powerful and easy pellet heating experience. The PelletPro, ESP, EASY Touch Control, and Wireless Room Sensor work in harmony to burn any grade of pellet with high efficiency and the smartest, most accurate temperature control and lowest maintenance.

Designed with true engineering excellence, Harman pellet inserts are built with our uncompromising commitment to quality and standard features that are worth the investment.

Features

- Smart operation with EASY Touch Control and Wireless Room Sensor
- Save money with built-in programmable thermostat
- View fuel levels easily with illuminated glass hopper lid
- · Burn any grade of pellet fuel
- Less loading with up to 64.5-lb hopper capacity
- · Easy, low maintenance
- Elegant flame-reactive mirrored glass

P42i-TC shown with optional surround extens



Accentra52i-TC

Specifications

Emissions..... 1.1 g/hr

Heating Capacity³...... 900-2,600 sq ft

64.5 lb Hopper

- 29-15/16" |*


Front View

41-13/16"

Hopper Capacity:

20" fireplace opening: 47.5 lb 24" fireplace opening: 64.5 lb Feed Rate: 1.5-5.8 lb/hr


Venting Size⁴: 4"



Clearance to Combustibles

A. Unit to sidewall	12"
B. Unit top to mantel	12"
C. Cast surround top to 3/4" trim	0"
D. Cast surround side to 3/4" trim	0"
E. Floor protector: spark and ember	

protection only (from glass)6"



Floor Protection: Minimum: 30"Wx 16-1/2"D

P₄2i-TC

Specifications

BTU/Hr Input¹............ 7,400-41,800

Efficiency²...... 84% LHV; 79% HHV

Emissions..... I.0 g/hr

Heating Capacity³...... 800-2,400 sq ft


Fuel Type..... Pellet

Weight...... 412 lb

Front View


Hopper Capacity:

20" fireplace opening: 47.5 lb 24" fireplace opening: 64.5 lb Feed Rate: .93-5.3 lb/hr Venting Size4: 4"



Clearance to Combustibles

A. Unit to sidewall12"
B. Unit top to mantel12"
C. Steel surround top to 3/4" trim0"
D. Steel surround side to 3/4" trim0"
E. Floor protector: spark and ember
protection only (from glass)6"



Floor Protection: Minimum: 30"W x 17"D

Pellet insert technologies



E.A.S.Y. Touch Control Easy. Accurate. Smart. Yearly Savings.—The Harman EASY Touch Control is the most advanced control system ever created and makes it easy to operate your insert, maintain accurate temperatures all day, every day, monitor performance and be notified when maintenance is needed, and save money on heating bills every year.



PelletPro™ Technology Burn any grade of pellet fuel with maximum heat and efficiency with this patented system. A bottom-up feed system burns each pellet completely and allows for 24-hour heating.



ESP Temperature Control Exhaust Sensing Probe (ESP) system delivers precise heat control, constantly monitoring and adjusting heat output to maintain set room temperatures within one degree.



Wireless Room Sensor Designed to communicate with the EASY Touch Controls on Harman pellet products from up to 30 feet away. Mounts on a wall wherever you want your heat measured.

Three easy steps to upgrade your existing wood-burning fireplace

STEP 1: MEASURE YOUR EXISTING FIREPLACE OPENING AND CHOOSE YOUR INSERT

The height, width and depth of the existing fireplace opening is needed to ensure selection of an appropriately-sized insert:

A. Fireplace front width _____

D. Fireplace depth

B. Fireplace front height _____

E. Hearth to mantel height

C. Fireplace back width

When choosing your model, keep these two factors in mind and you're sure to make a solid choice:

- Consider the size of your existing fireplace opening try and fill that space
- · Consider how your insert will be used: room size, heating needs and usage frequency all come into play

STEP 2: CHOOSE YOUR SURROUND

Surrounds fill the gap between the fireplace insert and existing fireplace opening. Both the Accentra52i-TC and the P42i-TC come standard with the small surround. Choose the surround extension (48"w \times 36"h) if you need the larger size, or custom sizes are available (up to 60"w \times 47"h).

STEP 3: CUSTOMIZE YOUR INSERT





Choose Matte Black or Majolica Brown Porcelain finish (Accentra52i-TC only)



Ceramic Log Kit



Service Rail Kit



Outside Temperature Kit



Zero Clearance Cabinet

(used to install where there is not a factory built fireplace or masonry fireplace)



Direct Vent Wall Pass-Through



Outside Air Termination Cap

Your Harman dealer is:



BY FORGE & FLAME

PHONE: 800-664-3119 WWW.HARMANSTOVES.COM



facebook.com/HarmanStoves youtube.com/HarmanStoves

HAR-1715U-0823

LIMITED LIFETIME WARRANTY⁶

The strongest in the industry, Harman provides a limited lifetime warranty on most important aspects: firebox and heat exchanger.

FPA tested input "Weighted average LHV (Low Heating Value) efficiency. HHV (High Heat Value) efficiency used to qualify products for Tax Credit beginning in 2021. See your local authorized Harman dealer for help in determining the product that bets suits your heating meets based on dimate and home efficiency. "When using 3" PL vent pipe, there must be 3" clearance to combustibles. For full warranty details, visit www.harmanstoves.com.

Actual product appearance, including flame, may differ from image. Product specifications and pricing subject to change without notice. The images and descriptions in this brochure are provided to assist you in product selection only. Fuel density and pellet shape may affect hopper capacity. BTUs may vary depending on type of fuel used. Refer to installation manual for complete clearance requirements and specifications.

Appliance surfaces get extremely HOT and can cause severe burns if touched. Keep a safe distance away. To learn more visit www.harmanstoves.com/fireplacesafety